




COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE



RECOMMENDED P.C.B. HOLE PATTERN (t=1.6±0.1)

HRS No.	PART NO.	NUMBER OF CONTACT	A	B	C	D
583-3000-5-71	PCN13-10S-2.54DSA(71)	10	26.42	21.42	16.42	10.16
583-3001-8-71	PCN13-16S-2.54DSA(71)	16	34.04	29.04	24.04	17.78
583-3002-0-71	PCN13-20S-2.54DSA(71)	20	39.12	34.12	29.12	22.86
583-3003-3-71	PCN13-30S-2.54DSA(71)	30	51.82	46.82	41.82	35.56
583-3004-6-71	PCN13-32S-2.54DSA(71)	32	54.36	49.36	44.36	38.10
583-3005-9-71	PCN13-44S-2.54DSA(71)	44	69.60	64.60	59.60	53.34
583-3006-1-71	PCN13-50S-2.54DSA(71)	50	77.22	72.22	67.22	60.96
583-3007-4-71	PCN13-64S-2.54DSA(71)	64	95.00	90.00	85.00	78.74
583-3008-7-71	PCN13-90S-2.54DSA(71)	90	128.02	123.02	118.02	111.76
583-3009-0-71	PCN13-100S-2.54DSA(71)	100	140.72	135.72	130.72	124.46

NOTE 1. AS FOR AUG, 2005.
2. THE DIMENSION IN PARENTHESIS IS FOR REFERENCE.

2	COPPER ALLOY	CONTACT AREA: Ni1μm+Au0.1μm
1	PBT	MOUNTING AREA: Ni1μm+Sn2μm
NO.	MATERIAL	BEIGE, UL94V-0

CODE NO. (OLD)	CL	DRAWN	M. OGAWA	DESIGNED	H. SAITOU	CHECKED	S. Yamada	APPROVED	K. Hayama	RELEASED
		05.08.29		05.08.29		05.08.30		05.08.30		

DRAWING NO.	EDC3-154139-01	PART NO.	PCN13-S-S-2.54DSA(72)
-------------	----------------	----------	-----------------------

SCALE	2:1	CODE NO.	CL583
UNITS	mm	HIROSE ELECTRIC CO., LTD.	

TO			
----	--	--	--